

Product Name: LANOX-mx4
Page: 1 of 6

This version issued: February, 2022

# Section 1 - Identification of the Material and Supplier

Candan Industries Pty. Ltd

Telephone: (07) 3209 8733

65 Chetwynd St

Fax: (07) 3209 8744

Loganholme QLD 4129 AUSTRALIA

Emergency Telephone number (A/HR) 0439 788 748

**New Zealand Supplier: INOX New Zealand** 

In New Zealand: Emergency 0212 811 500

In New Zealand: Phone 0212 811 500, Fax 09 929 3177

Chemical nature: Lubricant

Trade Name: LANOX-mx4

**Product Code:** 00104 (750 mL), 00102 (5 L), 00103 (20 L), 00107 (205 L)

**Product Use:** Heavy duty anti-corrosion lanolin based lubricant

Creation Date: December, 2016

This version issued: February, 2022 and is valid for 5 years from this date. Poisons Information Centre: Phone 13 11 26 from anywhere in Australia

# **Section 2 - Hazards Identification**

#### **Statement of Hazardous Nature**

This product is classified as: Hazardous according to the criteria of SWA.

Not a Dangerous Good according to Australian Dangerous Goods (ADG) Code, IATA or IMDG/IMSBC criteria.

SUSMP Classification: None allocated.

ADG Classification: None allocated. Not a Dangerous Good according to Australian Dangerous Goods (ADG)

Code, IATA or IMDG/IMSBC criteria. **UN Number:** None allocated



# **GHS Signal word: WARNING**

Aspiration Hazard Category 1

#### **HAZARD STATEMENT:**

H304: May be fatal if swallowed and enters airways.

#### **PREVENTION**

P210: Keep away from heat, sparks, open flames and hot surfaces. - No smoking.

P262: Do not get in eyes, on skin, or on clothing.

P281: Use personal protective equipment as required.

# RESPONSE

P331: Do NOT induce vomiting.

P362: Take off contaminated clothing and wash before reuse.

P301+P310: IF SWALLOWED: Immediately call a POISON CENTRE or doctor. P301+P330+P331: IF SWALLOWED: Rinse mouth. Do NOT induce vomiting.

P370+P378: In case of fire, use carbon dioxide, dry chemical, foam.

#### **STORAGE**

P405: Store locked up.

P410: Protect from sunlight.

P402+P404: Store in a dry place. Store in a closed container.

P403+P235: Store in a well-ventilated place. Keep cool.

# **DISPOSAL**

P501: If they can not be recycled, dispose of contents to an approved waste disposal plant and containers to landfill (see Section 13 of this SDS).

# **Statement of Hazardous Nature (New Zealand)**

#### SAFETY DATA SHEET

Issued by: Candan Industries Pty. Ltd

Telephone: (07) 3209 8733
In New Zealand: Emergency 0212 811 500
In New Zealand: Phone 0212 811 500, Fax 09 929 3177



Product Name: LANOX-mx4
Page: 2 of 6

This version issued: February, 2022

HSR002605 Lubricants Low Hazard Group Standard 2020

**DG Classification:** Not classified as a Dangerous Good for transport in accordance with the Land Transport Rule Dangerous Goods 2005 and NZS 5433:2007.

# **Emergency Overview**

Physical Description & Colour: Tan liquid

Odour: Faint lanolin odour

Major Health Hazards: if aspirated, may cause lung damage.

#### Section 3 - Composition/Information on Ingredients CAS No Conc. % TWA (mg/m<sup>3</sup>) STEL (mg/m<sup>3</sup>) Ingredients Mineral spirit 64742-47-8 <25 not set not set Other non hazardous ingredients to 100 not set secret not set

This is a commercial product whose exact ratio of components may vary slightly. Minor quantities of other non hazardous ingredients are also possible.

The SWA TWA exposure value is the average airborne concentration of a particular substance when calculated over a normal 8 hour working day for a 5 day working week. The STEL (Short Term Exposure Limit) is an exposure value that may be equalled (but should not be exceeded) for no longer than 15 minutes and should not be repeated more than 4 times per day. There should be at least 60 minutes between successive exposures at the STEL. The term "peak "is used when the TWA limit, because of the rapid action of the substance, should never be exceeded, even briefly.

### **Section 4 - First Aid Measures**

#### General Information:

You should call The Poisons Information Centre if you feel that you may have been poisoned, burned or irritated by this product. The number is 13 11 26 from anywhere in Australia (0800 764 766 in New Zealand) and is available at all times. Have this SDS with you when you call.

**Inhalation:** No first aid measures normally required. However, if inhalation has occurred, and irritation has developed, remove to fresh air and observe until recovered. If irritation becomes painful or persists more than about 30 minutes, seek medical advice.

**Skin Contact:** Wash gently and thoroughly with water (use non-abrasive soap if necessary) for 5 minutes or until chemical is removed.

**Eye Contact:** Immediately flush the contaminated eye(s) with lukewarm, gently flowing water for 5 minutes or until the product is removed, while holding the eyelid(s) open. Obtain medical advice immediately if irritation occurs. Take special care if exposed person is wearing contact lenses.

**Ingestion:** If swallowed, do NOT induce vomiting. Wash mouth with water and contact a Poisons Information Centre, or call a doctor.

# **Section 5 - Fire Fighting Measures**

**Fire and Explosion Hazards**: The major hazard in fires is usually inhalation of heated and toxic or oxygen deficient (or both), fire gases. There is no risk of an explosion from this product under normal circumstances if it is involved in a fire.

Fire decomposition products from this product may be toxic if inhaled. Take appropriate protective measures.

**Extinguishing Media:** In case of fire, use carbon dioxide, dry chemical, foam.

**Fire Fighting:** If a significant quantity of this product is involved in a fire, call the fire brigade.

Flammability Class: Not flammable (GHS); C2 combustible (AS 1940)

#### **Section 6 - Accidental Release Measures**

**Accidental release:** In the event of a major spill, prevent spillage from entering drains or water courses. As a minimum, wear overalls, goggles and gloves. No special recommendations for clothing materials. Eye/face protective equipment should comprise, as a minimum, protective glasses and, preferably, goggles. If there is a significant chance that vapours or mists are likely to build up in the cleanup area, we recommend that you use a respirator. Usually, no respirator is necessary when using this product. However, if you have any doubts consult the Australian Standard mentioned below (section 8). Otherwise, not normally necessary.

Stop leak if safe to do so, and contain spill. Absorb onto sand, vermiculite or other suitable absorbent material. If spill is too large or if absorbent material is not available, try to create a dike to stop material spreading or going into drains or waterways. Sweep up and shovel or collect recoverable product into labelled containers for recycling or salvage,

#### SAFETY DATA SHEET

Issued by: Candan Industries Pty. Ltd

Telephone: (07) 3209 8733
In New Zealand: Emergency 0212 811 500
In New Zealand: Phone 0212 811 500, Fax 09 929 3177



Product Name: LANOX-mx4

Page: 3 of 6

This version issued: February, 2022

and dispose of promptly. Recycle containers wherever possible after careful cleaning. After spills, wash area preventing runoff from entering drains. If a significant quantity of material enters drains, advise emergency services. This material may be suitable for approved landfill. Ensure legality of disposal by consulting regulations prior to disposal. Thoroughly launder protective clothing before storage or re-use. Advise laundry of nature of contamination when sending contaminated clothing to laundry.

# Section 7 - Handling and Storage

**Handling:** Keep exposure to this product to a minimum, and minimise the quantities kept in work areas. Check Section 8 of this SDS for details of personal protective measures, and make sure that those measures are followed. The measures detailed below under "Storage" should be followed during handling in order to minimise risks to persons using the product in the workplace. Also, avoid contact or contamination of product with incompatible materials listed in Section 10.

**Storage:** Store packages of this product in a cool place. Keep containers dry and away from water. Keep containers of this product in a well ventilated area. Keep away from sources of ignition such as sparks and open flames. Protect this product from light. Make sure that the product does not come into contact with substances listed under "Incompatibilities" in Section 10. Some liquid preparations settle or separate on standing and may require stirring before use. Check packaging - there may be further storage instructions on the label.

# **Section 8 - Exposure Controls and Personal Protection**

The following Australian Standards will provide general advice regarding safety clothing and equipment:

Respiratory equipment: **AS/NZS 1715**, Protective Gloves: **AS 2161**, Occupational Protective Clothing: AS/NZS 4501 set 2008, Industrial Eye Protection: **AS1336** and **AS/NZS 1337**, Occupational Protective Footwear: **AS/NZS2210**. Exposure limits have not been established by SWA for any of the significant ingredients in this product.

No special equipment is usually needed when occasionally handling small quantities. The following instructions are for bulk handling or where regular exposure in an occupational setting occurs without proper containment systems.

**Ventilation:** This product should only be used in a well ventilated area. If natural ventilation is inadequate, use of a fan is suggested.

**Eye Protection:** Eye protection such as protective glasses or goggles is recommended when this product is being used.

**Skin Protection:** You should avoid contact even with mild skin irritants. Therefore you should wear suitable impervious elbow-length gloves and facial protection when handling this product. See below for suitable material types.

**Protective Material Types:** There is no specific recommendation for any particular protective material type. **Respirator:** Usually, no respirator is necessary when using this product. However, if you have any doubts consult the Australian Standard mentioned above. Otherwise, not normally necessary.

# **Section 9 - Physical and Chemical Properties:**

Physical Description & colour: Tan liquid

Flash point:

Odour: Faint lanolin odour Boiling Point: Not available.

179°C

**Upper Flammability Limit:** No data. **Lower Flammability Limit:** No data. **Autoignition temperature:** No data. **Freezing/Melting Point:** -26°C Volatiles: No data. **Vapour Pressure:** No data. **Vapour Density:** No data. Specific Gravity: 0.8461 Water Solubility: Negligible. pH: No data. Volatility: No data. **Odour Threshold:** No data. **Evaporation Rate:** No data. Coeff Oil/water Distribution: No data

#### SAFETY DATA SHEET

Issued by: Candan Industries Pty. Ltd

Telephone: (07) 3209 8733
In New Zealand: Phone 0212 811 500, Fax 09 929 3177



Product Name: LANOX-mx4
Page: 4 of 6

This version issued: February, 2022

Particle Characteristics: Not applicable for liquids.

# Section 10 - Stability and Reactivity

**Reactivity:** This product is unlikely to react or decompose under normal storage conditions. However, if you have any doubts, contact the supplier for advice on shelf life properties.

**Conditions to Avoid:** This product should be kept in a cool place, preferably below 30°C. Containers should be kept dry. Keep containers and surrounding areas well ventilated. Keep away from sources of sparks or ignition. Protect this product from light.

**Incompatibilities:** strong oxidising agents, aerosols, corrosive liquids.

**Fire Decomposition:** Combustion forms carbon dioxide, and if incomplete, carbon monoxide and possibly smoke. Water is also formed. Carbon monoxide poisoning produces headache, weakness, nausea, dizziness, confusion, dimness of vision, disturbance of judgment, and unconsciousness followed by coma and death.

**Polymerisation:** This product will not undergo polymerisation reactions.

# **Section 11 - Toxicological Information**

**Toxicity:** A summary of white spirit type hydrocarbons can be found at http://www.inchem.org/documents/ehc/ehc/ehc187.htm

Ingestion of white spirit has been reported to produce gastrointestinal irritation with pain, vomiting and diarrhoea. Lesions of the mucous membranes in the oesophagus and the gastrointestinal tract followed the oral exposure. Owing to its low viscosity and low surface tension, white spirit poses a risk of aspiration into the lungs following oral exposure. A few mL of solvent aspirated into the lungs are able to produce serious bronchopneumonia and 10-30mL may be fatal.

Prolonged dermal exposure to white spirit, e.g., resulting from wearing clothes that have been soaked or moistened by white spirit for hours, may produce irritation and dermatitis.

Single cases of acute toxicity to the kidney, liver and bone marrow have been reported following exposure to white spirit at high levels. However, owing to lack of details and the sporadic nature of the reports, the relevance of these findings is unclear.

Inhalation of aliphatic hydrocarbon vapours seems to show little toxicity, but the vapours are CNS depressants and have a disinhibiting euphoric effect.

#### **Potential Health Effects**

### Inhalation:

**Short Term Exposure:** Available data indicates that this product is not harmful. However product may be mildly irritating, although unlikely to cause anything more than mild transient discomfort.

Long Term Exposure: No data for health effects associated with long term inhalation.

#### **Skin Contact:**

**Short Term Exposure:** Available data indicates that this product is not harmful. It should present no hazards in normal use. However product may be irritating, but is unlikely to cause anything more than mild transient discomfort. **Long Term Exposure:** No data for health effects associated with long term skin exposure.

#### **Eye Contact:**

**Short Term Exposure:** This product is believed to be mildly irritating, to eyes, but is unlikely to cause anything more than mild transient discomfort.

**Long Term Exposure:** No data for health effects associated with long term eye exposure.

### Ingestion:

**Short Term Exposure:** Significant oral exposure is considered to be unlikely. Because of the low viscosity of this product, it may directly enter the lungs if swallowed, or if subsequently vomited. Once in the lungs, it is very difficult to remove and can cause severe injury or death. However, this product may be irritating to mucous membranes but is unlikely to cause anything more than transient discomfort.

Long Term Exposure: No data for health effects associated with long term ingestion.

#### Carcinogen Status:

**SWA:** No significant ingredient is classified as carcinogenic by SWA. **NTP:** No significant ingredient is classified as carcinogenic by NTP. **IARC:** No significant ingredient is classified as carcinogenic by IARC.

# **SAFETY DATA SHEET**

Issued by: Candan Industries Pty. Ltd

Telephone: (07) 3209 8733
In New Zealand: Emergency 0212 811 500
In New Zealand: Phone 0212 811 500, Fax 09 929 3177

Poisons Information Centre: 13 11 26 from anywhere in Australia and 0800 764 766 in New Zealand



Product Name: LANOX-mx4
Page: 5 of 6

This version issued: February, 2022

# **Section 12 - Ecological Information**

Insufficient data to be sure of status.

Biodegradation is expected to be the primary fate process for aliphatic hydrocarbons in soil and water. The rate and extent of biodegradation are dependent on the ambient temperature, the presence of a sufficient number of microorganisms capable of metabolizing the hydrocarbons and the concentration of white spirit in or on the soil or water.

Biodegradation of C7 to C12 hydrocarbons is expected to be significant under environmental conditions favourable to microbial oxidation. Naturally occurring hydrocarbon-degrading microorganisms have been isolated from polluted soil and, to a lesser extent, non-polluted soil.

The low water solubility and moderate vapour pressure of white spirit (Stoddard solvent) suggest that volatilization and subsequent photo-oxidation are important processes for abiotic degradation in the atmosphere.

The octanol/water partition coefficient (log Pow) of white spirit (17% v/v aromatics) has been found to be 3.5 to 6.4. This indicates a moderate potential for bioaccumulation by organisms from water and a likelihood of partitioning to fat within organisms.

# **Section 13 - Disposal Considerations**

**Disposal:** This product may be recycled if unused, or if it has not been contaminated so as to make it unsuitable for its intended use. If it has been contaminated, it may be possible to reclaim the product by filtration, distillation or some other means. If neither of these options is suitable in-house, consider controlled incineration, or contact a specialist waste disposal company.

# **Section 14 - Transport Information**

**UN Number:** This product is not classified as a Dangerous Good by ADG, IATA or IMDG/IMSBC criteria. No special transport conditions are necessary unless required by other regulations.

# Section 15 - Regulatory Information

**AllC:** All of the significant ingredients in this formulation are compliant with AlCIS regulations.

#### **New Zealand:**

HSR002605 Lubricants Low Hazard Group Standard 2020

#### Section 16 - Other Information

This SDS contains only safety-related information. For other data see product literature.

Acronyms:

**ADG Code** Australian Code for the Transport of Dangerous Goods by Road and Rail (7<sup>th</sup> edition)

AllC Australian Inventory of Industrial Chemicals

SWA Safe Work Australia, formerly ASCC and NOHSC

CAS number Chemical Abstracts Service Registry Number

Hazchem Code Emergency action code of numbers and letters that provide information to emergency

services especially firefighters

IARC International Agency for Research on Cancer

NOS Not otherwise specified

NTP National Toxicology Program (USA)

SUSMP Standard for the Uniform Scheduling of Medicines & Poisons

**UN Number** United Nations Number

THIS SDS SUMMARISES OUR BEST KNOWLEDGE OF THE HEALTH AND SAFETY HAZARD INFORMATION OF THE PRODUCT AND HOW TO SAFELY HANDLE AND USE THE PRODUCT IN THE WORKPLACE. EACH USER MUST REVIEW THIS SDS IN THE CONTEXT OF HOW THE PRODUCT WILL BE HANDLED AND USED IN THE WORKPLACE.

IF CLARIFICATION OR FURTHER INFORMATION IS NEEDED TO ENSURE THAT AN APPROPRIATE RISK ASSESSMENT CAN BE MADE, THE USER SHOULD CONTACT THIS COMPANY SO WE CAN ATTEMPT TO OBTAIN ADDITIONAL INFORMATION FROM OUR SUPPLIERS OUR RESPONSIBILITY FOR PRODUCTS SOLD IS SUBJECT TO OUR STANDARD TERMS AND CONDITIONS, A COPY OF WHICH IS SENT TO OUR CUSTOMERS AND IS ALSO AVAILABLE ON REQUEST.

Please read all labels carefully before using product.

#### SAFETY DATA SHEET

Issued by: Candan Industries Pty. Ltd

Telephone: (07) 3209 8733
In New Zealand: Emergency 0212 811 500
In New Zealand: Phone 0212 811 500, Fax 09 929 3177



Product Name: LANOX-mx4
Page: 6 of 6

This version issued: February, 2022

# Australia:

This SDS is prepared in accord with the SWA document "Preparation of Safety Data Sheets for Hazardous Chemicals - Code of Practice" (July 2020) and GHS Revision 7

### **New Zealand**

HSNO Approved Code of Practice: Preparation of Safety Data Sheets. New Zealand Chemical Industry Council September 2006.

Telephone: (07) 3209 8733