

Safety Data Sheet

According To Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules And Regulations And According To The Hazardous

Products Regulation (February 11, 2015).

Revision Date: 01/20/2017 Date of Issue: 01/20/2017 Version: 1.0

SECTION 1: IDENTIFICATION

<u>Product Identifier</u>

Product Form: Mixture

Product Name: Tea Tree Oil Spray Product Code: 965XX-SPRAY Intended Use of the Product

Air Freshener

Name, Address, and Telephone of the Responsible Party

Starbrite® Inc.

4041 SW 47th Avenue Fort Lauderdale, FL 33314

(954)587-6280 www.starbrite.com

Emergency Telephone Number

Emergency Number : US: (800) 424-9300; International: (703) 527-3887 (CHEMTREC)

SECTION 2: HAZARDS IDENTIFICATION

Classification of the Substance or Mixture

GHS-US/CA Classification

Flam. Liq. 3 H226 Skin Irrit. 2 H315 Skin Sens. 1 H317

Full text of hazard classes and H-statements: see section 16

Label Elements

GHS-US/CA Labeling

Hazard Pictograms (GHS-US/CA)





Signal Word (GHS-US/CA) : Warning

Hazard Statements (GHS-US/CA) : H226 - Flammable liquid and vapor.

H315 - Causes skin irritation.

H317 - May cause an allergic skin reaction.

Precautionary Statements (GHS-US/CA): P210 - Keep away from heat, hot surfaces, sparks, open flames and other ignition

sources. No smoking.

P233 - Keep container tightly closed.

P240 - Ground/bond container and receiving equipment.

P241 - Use explosion-proof electrical, ventilating, and lighting equipment.

P242 - Use only non-sparking tools.

P243 - Take precautionary measures against static discharge.

P261 - Avoid breathing vapors, mist, or spray.

P264 - Wash hands, forearms, and other exposed areas thoroughly after handling. P272 - Contaminated work clothing should not be allowed out of the workplace.

P280 - Wear protective gloves, protective clothing, and eye protection.

P303+P361+P353 - IF ON SKIN (or hair): Take off immediately all contaminated clothing.

Rinse skin with water.

P321 - Specific treatment (see section 4 on this SDS).

P333+P313 - If skin irritation or rash occurs: Get medical advice/attention. P362+P364 - Take off contaminated clothing and wash it before reuse.

01/20/2017 IRPTT.B-CC EN (English US) 1/10

Safety Data Sheet

According To Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules And Regulations And According To The Hazardous Products Regulation (February 11, 2015).

P370+P378 - In case of fire: Use appropriate media (see section 5) to extinguish.

P403+P235 - Store in a well-ventilated place. Keep cool.

P501 - Dispose of contents/container in accordance with local, regional, national, territorial, provincial, and international regulations.

Other Hazards

Aquatic Acute 3 H402 Aquatic Chronic 3 H412 H402 - Harmful to aquatic life.

H412 - Harmful to aquatic life with long lasting effects.

P273 - Avoid release to the environment.

Exposure may aggravate pre-existing eye, skin, or respiratory conditions.

Unknown Acute Toxicity (GHS-US/CA)

No data available

SECTION 3: COMPOSITION/INFORMATION ON INGREDIENTS

Mixture

Name	Product Identifier	% *	GHS Ingredient Classification
Oils, tea-tree	(CAS No) 68647-73-4	6 - < 10	Flam. Liq. 3, H226
			Acute Tox. 4 (Oral), H302
			Skin Irrit. 2, H315
			Skin Sens. 1, H317
			Asp. Tox. 1, H304
			Aquatic Acute 2, H401
			Aquatic Chronic 2, H411
Isopropyl alcohol	(CAS No) 67-63-0	< 0.4	Flam. Liq. 2, H225
			Eye Irrit. 2A, H319
			STOT SE 3, H336
Oils, lemongrass	(CAS No) 8007-02-1	0.05 - 0.2	Flam. Liq. 4, H227
			Skin Irrit. 2, H315
			Eye Irrit. 2A, H319
			Skin Sens. 1, H317
			Aquatic Chronic 2, H411

Full text of H-phrases: see section 16

SECTION 4: FIRST AID MEASURES

Description of First-aid Measures

General: Never give anything by mouth to an unconscious person. If you feel unwell, seek medical advice (show the label where possible).

Inhalation: When symptoms occur: go into open air and ventilate suspected area. Obtain medical attention if breathing difficulty persists.

Skin Contact: Remove contaminated clothing. Drench affected area with water for at least 15 minutes. Obtain medical attention if irritation develops or persists.

Eye Contact: Rinse cautiously with water for at least 15 minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Obtain medical attention.

Ingestion: Do NOT induce vomiting. Rinse mouth. Immediately call a POISON CENTER or doctor/physician.

Most Important Symptoms and Effects Both Acute and Delayed

General: Causes skin irritation. Skin sensitization. **Inhalation:** Prolonged exposure may cause irritation.

Skin Contact: Redness, pain, swelling, itching, burning, dryness, and dermatitis. May cause an allergic skin reaction.

Eye Contact: May cause slight irritation to eyes.

Ingestion: Ingestion is likely to be harmful or have adverse effects.

01/20/2017 IRPTT.B-CC EN (English US) 2/10

^{*}Percentages are listed in weight by weight percentage (w/w%) for liquid and solid ingredients. Gas ingredients are listed in volume by volume percentage (v/v%).

Safety Data Sheet

According To Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules And Regulations And According To The Hazardous Products Regulation (February 11, 2015).

Chronic Symptoms: None known.

Indication of Any Immediate Medical Attention and Special Treatment Needed

If exposed or concerned, get medical advice and attention. If medical advice is needed, have product container or label at hand.

SECTION 5: FIRE FIGHTING MEASURES

Extinguishing Media

Suitable Extinguishing Media: Dry chemical powder, alcohol-resistant foam, carbon dioxide (CO₂). Water may be ineffective but water should be used to keep fire-exposed container cool.

Unsuitable Extinguishing Media: Do not use a heavy water stream. A heavy water stream may spread burning liquid.

Special Hazards Arising From the Substance or Mixture

Fire Hazard: Flammable liquid and vapor.

Explosion Hazard: May form flammable or explosive vapor-air mixture. When mixed with air and exposed to an ignition source, flammable vapors can burn in the open or explode in confined spaces. Being heavier than air, vapors may travel long distances to an ignition source and flash back. Runoff to sewer may cause fire or explosion hazard.

Reactivity: Reacts violently with strong oxidizers. Increased risk of fire or explosion.

Advice for Firefighters

Precautionary Measures Fire: Exercise caution when fighting any chemical fire.

Firefighting Instructions: Use water spray or fog for cooling exposed containers. In case of major fire and large quantities: Evacuate area. Fight fire remotely due to the risk of explosion. Remove containers from fire area if this can be done without risk.

Protection During Firefighting: Do not enter fire area without proper protective equipment, including respiratory protection.

Hazardous Combustion Products: Thermal decomposition generates: Carbon oxides (CO, CO₂). Nitrogen oxides. Hydrocarbons.

Oxides of magnesium. Irritating fumes.

Other Information: Do not allow run-off from fire fighting to enter drains or water courses.

Reference to Other Sections

Refer to Section 9 for flammability properties.

SECTION 6: ACCIDENTAL RELEASE MEASURES

Personal Precautions, Protective Equipment and Emergency Procedures

General Measures: Avoid breathing (vapor, mist, spray). Do not get in eyes, on skin, or on clothing. Keep away from heat, hot surfaces, sparks, open flames, and other ignition sources. No smoking. Use special care to avoid static electric charges.

For Non-Emergency Personnel

Protective Equipment: Use appropriate personal protective equipment (PPE).

Emergency Procedures: Evacuate unnecessary personnel. Stop leak if safe to do so.

For Emergency Personnel

Protective Equipment: Equip cleanup crew with proper protection.

Emergency Procedures: Ventilate area. Eliminate ignition sources. Upon arrival at the scene, a first responder is expected to recognize the presence of dangerous goods, protect oneself and the public, secure the area, and call for the assistance of trained personnel as soon as conditions permit.

Environmental Precautions

Prevent entry to sewers and public waters. Avoid release to the environment.

Methods and Materials for Containment and Cleaning Up

For Containment: Contain any spills with dikes or absorbents to prevent migration and entry into sewers or streams. As an immediate precautionary measure, isolate spill or leak area in all directions.

Methods for Cleaning Up: Clean up spills immediately and dispose of waste safely. Eliminate all ignition sources. Absorb and/or contain spill with inert material. Do not take up in combustible material such as: saw dust or cellulosic material. Use only non-sparking tools. Transfer spilled material to a suitable container for disposal. Contact competent authorities after a spill.

Reference to Other Sections

See Section 8 for exposure controls and personal protection and Section 13 for disposal considerations.

SECTION 7: HANDLING AND STORAGE

Precautions for Safe Handling

Additional Hazards When Processed: Handle empty containers with care because residual vapors are flammable.

Precautions for Safe Handling: Wash hands and other exposed areas with mild soap and water before eating, drinking or smoking and when leaving work. Avoid prolonged contact with eyes, skin and clothing. Avoid breathing vapors, mist, and spray. Take precautionary measures against static discharge. Use only non-sparking tools. Use appropriate personal protective equipment (PPE).

01/20/2017 IRPTT.B-CC EN (English US) 3/10

Safety Data Sheet

According To Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules And Regulations And According To The Hazardous Products Regulation (February 11, 2015).

Hygiene Measures: Handle in accordance with good industrial hygiene and safety procedures.

Conditions for Safe Storage, Including Any Incompatibilities

Technical Measures: Comply with applicable regulations. Take action to prevent static discharges. Ground and bond container and receiving equipment. Use explosion-proof electrical, ventilating, and lighting equipment.

Storage Conditions: Store in a dry, cool place. Store in a well-ventilated place. Keep container tightly closed. Containers which are opened should be properly resealed and kept upright to prevent leakage. Keep/Store away from direct sunlight, extremely high or low temperatures and incompatible materials. Keep in fireproof place.

Incompatible Materials: Strong acids, strong bases, strong oxidizers. Reducing agents.

Specific End Use(s)

Air Freshener

SECTION 8: EXPOSURE CONTROLS/PERSONAL PROTECTION

Control Parameters

For substances listed in section 3 that are not listed here, there are no established Exposure limits from the manufacturer, supplier, importer, or the appropriate advisory agency including: ACGIH (TLV), AIHA (WEEL), NIOSH (REL), OSHA (PEL), Canadian provincial governments, or the Mexican government.

governments, or the wickled	Boteriment	
Isopropyl alcohol (67-63-0)		
Mexico	OEL TWA (mg/m³)	980 mg/m³
Mexico	OEL TWA (ppm)	400 ppm
Mexico	OEL STEL (mg/m³)	1225 mg/m³
Mexico	OEL STEL (ppm)	500 ppm
USA ACGIH	ACGIH TWA (ppm)	200 ppm
USA ACGIH	ACGIH STEL (ppm)	400 ppm
USA ACGIH	ACGIH chemical category	Not Classifiable as a Human Carcinogen
USA ACGIH	Biological Exposure Indices (BEI)	40 mg/l Parameter: Acetone - Medium: urine - Sampling
		time: end of shift at end of workweek (background,
		nonspecific)
USA OSHA	OSHA PEL (TWA) (mg/m³)	980 mg/m³
USA OSHA	OSHA PEL (TWA) (ppm)	400 ppm
USA NIOSH	NIOSH REL (TWA) (mg/m³)	980 mg/m³
USA NIOSH	NIOSH REL (TWA) (ppm)	400 ppm
USA NIOSH	NIOSH REL (STEL) (mg/m³)	1225 mg/m³
USA NIOSH	NIOSH REL (STEL) (ppm)	500 ppm
USA IDLH	US IDLH (ppm)	2000 ppm (10% LEL)
Alberta	OEL STEL (mg/m³)	984 mg/m³
Alberta	OEL STEL (ppm)	400 ppm
Alberta	OEL TWA (mg/m³)	492 mg/m³
Alberta	OEL TWA (ppm)	200 ppm
British Columbia	OEL STEL (ppm)	400 ppm
British Columbia	OEL TWA (ppm)	200 ppm
Manitoba	OEL STEL (ppm)	400 ppm
Manitoba	OEL TWA (ppm)	200 ppm
New Brunswick	OEL STEL (mg/m³)	1230 mg/m³
New Brunswick	OEL STEL (ppm)	500 ppm
New Brunswick	OEL TWA (mg/m³)	983 mg/m³
New Brunswick	OEL TWA (ppm)	400 ppm
Newfoundland & Labrador	OEL STEL (ppm)	400 ppm
Newfoundland & Labrador	OEL TWA (ppm)	200 ppm
Nova Scotia	OEL STEL (ppm)	400 ppm
Nova Scotia	OEL TWA (ppm)	200 ppm
Nunavut	OEL STEL (ppm)	400 ppm
Nunavut	OEL TWA (ppm)	200 ppm
Northwest Territories	OEL STEL (ppm)	400 ppm

01/20/2017 IRPTT.B-CC EN (English US) 4/10

Safety Data Sheet

According To Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules And Regulations And According To The Hazardous Products Regulation (February 11, 2015).

Northwest Territories	OEL TWA (ppm)	200 ppm
Ontario	OEL STEL (ppm)	400 ppm
Ontario	OEL TWA (ppm)	200 ppm
Prince Edward Island	OEL STEL (ppm)	400 ppm
Prince Edward Island	OEL TWA (ppm)	200 ppm
Québec	VECD (mg/m³)	1230 mg/m³
Québec	VECD (ppm)	500 ppm
Québec	VEMP (mg/m³)	985 mg/m³
Québec	VEMP (ppm)	400 ppm
Saskatchewan	OEL STEL (ppm)	400 ppm
Saskatchewan	OEL TWA (ppm)	200 ppm
Yukon	OEL STEL (mg/m³)	1225 mg/m³
Yukon	OEL STEL (ppm)	500 ppm
Yukon	OEL TWA (mg/m³)	980 mg/m³
Yukon	OEL TWA (ppm)	400 ppm

Exposure Controls

Appropriate Engineering Controls: Emergency eye wash fountains and safety showers should be available in the immediate vicinity of any potential exposure. Ensure adequate ventilation, especially in confined areas. Gas detectors should be used when flammable gases or vapors may be released. Proper grounding procedures to avoid static electricity should be followed. Use explosion-proof equipment. Ensure all national/local regulations are observed.

Personal Protective Equipment: Gloves. Protective clothing. Protective goggles. Insufficient ventilation: wear respiratory protection.









Materials for Protective Clothing: Chemically resistant materials and fabrics. Wear fire/flame resistant/retardant clothing.

Hand Protection: Wear protective gloves. **Eye Protection:** Chemical safety goggles.

Skin and Body Protection: Wear suitable protective clothing.

Respiratory Protection: In case of insufficient ventilation, wear suitable respiratory equipment.

Environmental Exposure Controls: Avoid release to the environment.

Other Information: When using, do not eat, drink or smoke.

SECTION 9: PHYSICAL AND CHEMICAL PROPERTIES

<u>Information on Basic Physical and Chemical Properties</u>

Physical State : Liquid

Appearance : Pale Yellow
Odor : Characteristic
Odor Threshold : Not available

pH : 9

Not available **Evaporation Rate Melting Point** Not available **Freezing Point** Not available **Boiling Point** Not available **Flash Point** 59.5 °C (139.1 °F) **Auto-ignition Temperature** Not available **Decomposition Temperature** Not available Flammability (solid, gas) Not available **Lower Flammable Limit** Not available **Upper Flammable Limit** Not available **Vapor Pressure** Not available

01/20/2017 IRPTT.B-CC EN (English US) 5/10

Safety Data Sheet

According To Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules And Regulations And According To The Hazardous Products Regulation (February 11, 2015).

Relative Vapor Density at 20°C : Not available Relative Density : Not available

Specific Gravity : 1

Solubility : Soluble in water.

Partition Coefficient: N-Octanol/Water : Not available

Viscosity : Not available

SECTION 10: STABILITY AND REACTIVITY

Reactivity: Reacts violently with strong oxidizers. Increased risk of fire or explosion.

Chemical Stability: Flammable liquid and vapor. May form flammable or explosive vapor-air mixture.

Possibility of Hazardous Reactions: Hazardous polymerization will not occur.

<u>Conditions to Avoid</u>: Direct sunlight, extremely high or low temperatures, heat, hot surfaces, sparks, open flames, incompatible

materials, and other ignition sources.

Incompatible Materials: Strong acids, strong bases, strong oxidizers. Reducing agents.

<u>Hazardous Decomposition Products</u>: Under normal conditions of storage and use, hazardous decomposition products should not

be produced.

SECTION 11: TOXICOLOGICAL INFORMATION

<u>Information on Toxicological Effects - Product</u>

Acute Toxicity (Oral): Not classified
Acute Toxicity (Dermal): Not classified
Acute Toxicity (Inhalation): Not classified

LD50 and LC50 Data: Not available

Skin Corrosion/Irritation: Causes skin irritation.

pH: 9

Eye Damage/Irritation: Not classified

pH: 9

Respiratory or Skin Sensitization: May cause an allergic skin reaction.

Germ Cell Mutagenicity: Not classified

Carcinogenicity: Not classified

Specific Target Organ Toxicity (Repeated Exposure): Not classified

Reproductive Toxicity: Not classified

Specific Target Organ Toxicity (Single Exposure): Not classified

Aspiration Hazard: Not classified.

Symptoms/Injuries After Inhalation: Prolonged exposure may cause irritation.

Symptoms/Injuries After Skin Contact: Redness, pain, swelling, itching, burning, dryness, and dermatitis. May cause an allergic skin

reaction.

Symptoms/Injuries After Eye Contact: May cause slight irritation to eyes.

Symptoms/Injuries After Ingestion: Ingestion is likely to be harmful or have adverse effects.

Chronic Symptoms: None known.

<u>Information on Toxicological Effects - Ingredient(s)</u>

LD50 and LC50 Data:

Isopropyl alcohol (67-63-0)	
LD50 Oral Rat	1870 mg/kg
LD50 Dermal Rabbit	4059 mg/kg
LC50 Inhalation Rat	72600 mg/m³ (Exposure time: 4 h)
LC50 Inhalation Rat	72.5 mg/l/4h
Oils, tea-tree (68647-73-4)	
LD50 Oral Rat	1.9 ml/kg
ATE US/CA (oral)	500.00 mg/kg body weight
Oils, lemongrass (8007-02-1)	
LD50 Oral Rat	> 5 g/kg

01/20/2017 IRPTT.B-CC EN (English US) 6/10

Safety Data Sheet

According To Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules And Regulations And According To The Hazardous Products Regulation (February 11, 2015).

LD50 Dermal Rabbit	> 5 g/kg
Isopropyl alcohol (67-63-0)	
IARC Group	3

SECTION 12: ECOLOGICAL INFORMATION

Toxicity

Ecology - General: Harmful to aquatic life. Harmful to aquatic life with long lasting effects.

Isopropyl alcohol (67-63-0)	
LC50 Fish 1	9640 mg/l (Exposure time: 96 h - Species: Pimephales promelas [flow-through])
EC50 Daphnia 1	13299 mg/l (Exposure time: 48 h - Species: Daphnia magna)
EC50 Other Aquatic Organisms 1	1000 mg/l (Exposure time: 96 h - Species: Desmodesmus subspicatus)
LC50 Fish 2	11130 mg/l (Exposure time: 96 h - Species: Pimephales promelas [static])
EC50 Other Aquatic Organisms 2	1000 mg/l (Exposure time: 72 h - Species: Desmodesmus subspicatus)

Persistence and Degradability

Tea Tree Oil -Spray	
Persistence and Degradability	May cause long-term adverse effects in the environment.

Bioaccumulative Potential

Tea Tree Oil -Spray	
Bioaccumulative Potential	Not established.
Isopropyl alcohol (67-63-0)	
Log Pow	0.05 (at 25 °C)

Mobility in Soil Not available

Other Adverse Effects

Other Information: Avoid release to the environment.

SECTION 13: DISPOSAL CONSIDERATIONS

Waste Disposal Recommendations: Dispose of contents/container in accordance with local, regional, national, territorial, provincial, and international regulations

Additional Information: Handle empty containers with care because residual vapors are flammable.

Ecology - Waste Materials: Avoid release to the environment. This material is hazardous to the aquatic environment. Keep out of sewers and waterways.

SECTION 14: TRANSPORT INFORMATION

The shipping description(s) stated herein were prepared in accordance with certain assumptions at the time the SDS was authored, and can vary based on a number of variables that may or may not have been known at the time the SDS was issued.

In Accordance with DOT

Proper Shipping Name : EXTRACTS, AROMATIC, LIQUID (Oils, tea-tree)

Hazard Class : 3
Identification Number : UN1169
Label Codes : 3

Packing Group : III
ERG Number : 127
Marine Pollutant : No

Additional Information : This product meets the limited quantities exemption as follows: DOT: Not regulated as dangerous goods when shipped in inner packagings equal to or less than 5L. Otherwise, the

above descriptions apply.

In Accordance with IMDG

Proper Shipping Name : EXTRACTS, AROMATIC, LIQUID (Oils, tea-tree)

Hazard Class : 3 **Identification Number** : UN1169

Label Codes: 3Packing Group: IIIEmS-No. (Fire): F-EEmS-No. (Spillage): S-D



01/20/2017 IRPTT.B-CC EN (English US) 7/10

Safety Data Sheet

According To Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules And Regulations And According To The Hazardous Products Regulation (February 11, 2015).

In Accordance with IATA

Proper Shipping Name : EXTRACTS, AROMATIC, LIQUID (Oils, tea-tree)

Identification Number : 3

Hazard Class : UN1169

Label Codes : 3
Packing Group : III
ERG Code (IATA) : 3L

In Accordance with TDG

Proper Shipping Name : EXTRACTS, AROMATIC, LIQUID (Oils, tea-tree)

Hazard Class : 3 Identification Number : UN1169

Label Codes : 3
Packing Group : III



SECTION 15: REGULATORY INFORMATION

US Federal Regulations

Tea Tree Oil -Spray	
SARA Section 311/312 Hazard Classes	Fire hazard
	Immediate (acute) health hazard
Isopropyl alcohol (67-63-0)	

Listed on the United States TSCA (Toxic Substances Control Act) inventory Subject to reporting requirements of United States SARA Section 313

SARA Section 313 - Emission Reporting1.0 % (only if manufactured by the strong acid process, no supplier notification)

Oils, tea-tree (68647-73-4)

Listed on the United States TSCA (Toxic Substances Control Act) inventory

Oils, lemongrass (8007-02-1)

Listed on the United States TSCA (Toxic Substances Control Act) inventory

US State Regulations

Isopropyl alcohol (67-63-0)

- U.S. California SCAQMD Toxic Air Contaminants Non-Cancer Acute
- U.S. California SCAQMD Toxic Air Contaminants Non-Cancer Chronic
- U.S. California Toxic Air Contaminant List (AB 1807, AB 2728)
- U.S. Connecticut Hazardous Air Pollutants HLVs (30 min)
- U.S. Connecticut Hazardous Air Pollutants HLVs (8 hr)
- U.S. Connecticut Volatile Substances
- U.S. Idaho Non-Carcinogenic Toxic Air Pollutants Acceptable Ambient Concentrations
- U.S. Idaho Non-Carcinogenic Toxic Air Pollutants Emission Levels (ELs)
- U.S. Idaho Occupational Exposure Limits TWAs
- RTK U.S. Massachusetts Right To Know List
- U.S. Massachusetts Toxics Use Reduction Act
- U.S. Michigan Occupational Exposure Limits STELs
- U.S. Michigan Occupational Exposure Limits TWAs
- U.S. Minnesota Hazardous Substance List
- U.S. Minnesota Permissible Exposure Limits STELs
- U.S. Minnesota Permissible Exposure Limits TWAs
- U.S. New Hampshire Regulated Toxic Air Pollutants Ambient Air Levels (AALs) 24-Hour
- U.S. New Hampshire Regulated Toxic Air Pollutants Ambient Air Levels (AALs) Annual
- U.S. New Jersey Discharge Prevention List of Hazardous Substances
- U.S. New Jersey Environmental Hazardous Substances List
- RTK U.S. New Jersey Right to Know Hazardous Substance List
- U.S. New Jersey Special Health Hazards Substances List
- U.S. New York Occupational Exposure Limits TWAs

01/20/2017 IRPTT.B-CC EN (English US) 8/10

Safety Data Sheet

According To Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules And Regulations And According To The Hazardous Products Regulation (February 11, 2015).

- U.S. North Dakota Air Pollutants Guideline Concentrations 1-Hour
- U.S. North Dakota Air Pollutants Guideline Concentrations 8-Hour
- U.S. Oregon Permissible Exposure Limits TWAs
- U.S. California Safer Consumer Products Initial List of Candidate Chemicals and Chemical Groups
- RTK U.S. Pennsylvania RTK (Right to Know) Environmental Hazard List
- RTK U.S. Pennsylvania RTK (Right to Know) List
- U.S. Rhode Island Air Toxics Acceptable Ambient Levels 1-Hour
- U.S. Tennessee Occupational Exposure Limits STELs
- U.S. Tennessee Occupational Exposure Limits TWAs
- U.S. Texas City of Austin Aerosol Paint and Glue Restrictions
- U.S. Texas Effects Screening Levels Long Term
- U.S. Texas Effects Screening Levels Short Term
- U.S. Vermont Permissible Exposure Limits STELs
- U.S. Vermont Permissible Exposure Limits TWAs
- U.S. Washington Permissible Exposure Limits STELs
- U.S. Washington Permissible Exposure Limits TWAs

Oils, lemongrass (8007-02-1)

- U.S. Texas Effects Screening Levels Long Term
- U.S. Texas Effects Screening Levels Short Term

Canadian Regulations

Isopropyl alcohol (67-63-0)

Listed on the Canadian DSL (Domestic Substances List)

Oils, tea-tree (68647-73-4)

Listed on the Canadian DSL (Domestic Substances List)

Oils, lemongrass (8007-02-1)

Listed on the Canadian DSL (Domestic Substances List)

SECTION 16: OTHER INFORMATION, INCLUDING DATE OF PREPARATION OR LAST REVISION

Revision Date : 01/20/2017

Other Information : This document has been prepared in accordance with the SDS requirements of the OSHA

Hazard Communication Standard 29 CFR 1910.1200 and Canada's Hazardous Products

Regulations (HPR).

GHS Full Text Phrases:

Acuto Tour 4 (Onel)	Aputa tavisitu (aral) Catagam A
Acute Tox. 4 (Oral)	Acute toxicity (oral) Category 4
Aquatic Acute 2	Hazardous to the aquatic environment - Acute Hazard Category 2
Aquatic Acute 3	Hazardous to the aquatic environment - Acute Hazard Category 3
Aquatic Chronic 2	Hazardous to the aquatic environment - Chronic Hazard Category 2
Aquatic Chronic 3	Hazardous to the aquatic environment - Chronic Hazard Category 3
Asp. Tox. 1	Aspiration hazard Category 1
Eye Irrit. 2A	Serious eye damage/eye irritation Category 2A
Flam. Liq. 2	Flammable liquids Category 2
Flam. Liq. 3	Flammable liquids Category 3
Flam. Liq. 4	Flammable liquids Category 4
Skin Irrit. 2	Skin corrosion/irritation Category 2
Skin Sens. 1	Skin sensitization Category 1
STOT SE 3	Specific target organ toxicity (single exposure) Category 3
H225	Highly flammable liquid and vapor
H226	Flammable liquid and vapor
H227	Combustible liquid
H302	Harmful if swallowed
H304	May be fatal if swallowed and enters airways

01/20/2017 IRPTT.B-CC EN (English US) 9/10

Safety Data Sheet

According To Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules And Regulations And According To The Hazardous Products Regulation (February 11, 2015).

H315	Causes skin irritation
H317	May cause an allergic skin reaction
H319	Causes serious eye irritation
H336	May cause drowsiness or dizziness
H401	Toxic to aquatic life
H402	Harmful to aquatic life
H411	Toxic to aquatic life with long lasting effects
H412	Harmful to aquatic life with long lasting effects

NFPA Health Hazard

: 2 - Intense or continued exposure could cause temporary incapacitation or possible residual injury unless prompt medical attention is given.


NFPA Fire Hazard

2 - Must be moderately heated or exposed to relatively high temperature before ignition can occur.

NFPA Reactivity Hazard

: 0 - Normally stable, even under fire exposure conditions,

and are not reactive with water.



This information is based on our current knowledge and is intended to describe the product for the purposes of health, safety and environmental requirements only. It should not therefore be construed as guaranteeing any specific property of the product.

NA GHS SDS 2015 (Can, US, Mex)

01/20/2017 IRPTT.B-CC EN (English US) 10/10